

KVF360 4X4

PERFECT MIDDLEWEIGHT



Model Year 2009

COLOURS



Sunbeam red



Woodsman green

FEATURES



RACKS



SWINGARM



Sealed rear brake



Hitch bracket

SPECIFICATIONS

Engine type	362 cm ³ , air-cooled, 4-stroke single
Bore x stroke	80 x 72 mm
Compression ratio	8.3:1
Valve/Induction system	SOHC, 2-valve cylinder-head
Maximum power	15,7 kW (21.4 PS)/7,000 rpm
Maximum torque	26.1 N·m /4,500 rpm
Fuel system	Carburetor: Keihin CVK34
Ignition	Digital DC-CDI
Starting	Electric starter with auxiliary recoil
Transmission	CVT with reverse
Final Drive	Gear Shaft (Selectable 4WD/2WD)
Suspension, front	MacPherson strut
Suspension, rear	Swingarm with single shock absorber
Wheel travel, front	170 mm
Wheel travel, rear	180 mm
Tyre, front	AT 25 x 8-12 (tubeless)
Tyre, rear	AT 25 x 10-12 (tubeless)
Brakes, front	166 mm discs with single piston calipers
Brakes, rear	Sealed multiplate system
Turning radius	3.1 m
Dimensions (L x W x H)	2,065 x 1,205 x 1,175 mm
Track width, front / rear	890 / 895 mm
Ground Clearance	250 / 195 mm (centre of chassis / rear final drive)
Rack Load Capacity, front / rear	40 kg / 70 kg
Towing Capacity	500 kg
Fuel capacity	13.5 litres
Dry weight	274.5 kg
Curb Mass	291 kg