

## KVF650 4X4

A PERFECT BALANCE OF PRICE AND PERFORMANCE



Model Year 2009

### COLOURS



Woodsman Green



Lime Green

### Features



MUDGUARD



OUTLETS



WET BRAKE



Limited slip differential

### specifications

Engine type	633 cm <sup>3</sup> , liquid-cooled, 4-stroke 90°
Bore x stroke	80 x 63 mm
Compression ratio	9.9:1
Valve/Induction system	4 valves per cylinder
Maximum power	30.9 kW (42 PS)/6,500 rpm
Maximum torque	52.1 N·m/4,000 rpm
Fuel system	Keihin CVKR-D32, 2 carburetors
Ignition	Digital DC-CDI
Starting	Electric with recoil back up
Transmission	CVT with reverse, selectable 4WD
Final Drive	2WD/4WD, shaft
Suspension, front	MacPherson strut
Suspension, rear	Swingarm with adjustable shock absorber
Wheel travel, front	170 mm
Wheel travel, rear	184 mm
Tyre, front	AT 25 x 8-12 (tubeless)
Tyre, rear	AT 25 x 10-12 (tubeless)
Brakes, front	200 mm discs with twin piston calipers
Brakes, rear	Sealed multi-plate system
Turning radius	3.1 m
Dimensions (L x W x H)	2,185 x 1,212 x 1,164 mm
Track width, front / rear	910 / 909 mm
Ground Clearance	229 / 185 mm (centre of chassis / rear final drive)
Rack Load Capacity, front / rear	Front 40 kg, rear 80 kg
Towing Capacity	567 kg
Fuel capacity	18 litres
Dry weight	273 kg
Curb Mass	294 kg