

KVF750 4X4

FAST, DEPENDABLE AGILE AND TOUGH!



Model Year 2009

COLOURS




Super black



Woodsman green

FEATURES



Stronger axle boots



Throttle



Dual-rate springs



Sealed storage

SPECIFICATIONS

Engine type	Liquid-cooled, 4-stroke 90o V-twin
Displacement	749 cm ³
Bore x stroke	85 x 66 mm
Compression ratio	8.8:1
Valve/Induction system	SOHC, 4 valves per cylinder
Maximum power	37.1 kW (50.4 PS) / 6,500 rpm
Maximum torque	59.4 N-m / 4,500 rpm
Fuel system	Fuel injection: φ36 mm x 2 (Mikuni)
Ignition	Battery & Coil (Transistorised ignition)
Starting	Electric
Transmission	Dual range CVT with reverse
Final Drive	2WD / 4WD, shaft
Frame type	Double cradle, high-tensile tubular steel
Suspension, front	Double wishbone with twin shock absorbers
Suspension, rear	Double wishbone with double shock absorbers
Wheel travel, front	171 mm
Wheel travel, rear	200 mm
Tyre, front	AT 25 x 8-12
Tyre, rear	AT 25 x 10-12
Brakes, front	Dual 200 mm discs with twin piston calipers
Brakes, rear	Sealed multi-plate system
Turning radius	3.2 m
Dimensions (L x W x H)	2,195 mm x 1,166 mm x 1,233 mm
Wheelbase	1,284 mm
Ground Clearance	247 mm
Rack Load Capacity, front / rear	Front: 40 kg, rear: 80 kg
Towing Capacity	5,560 N (567 kg)
Fuel capacity	19 litres
Dry weight	275 kg
Curb Mass	297 kg