

MULE 600

LIGHT, NIMBLE and ECONOMICAL



Model Year 2009

FEATURES

SPECIFICATIONS

Engine type	Air cooled, OHV, 4-stroke single
Displacement	401 cm ³
Maximum power	9.2 kW (12.5 PS)/3,800 rpm
Maximum torque	27.9N·m (2.8kgf·m)/2,200rpm
Transmission	1 speed automatic plus reverse
Final Drive	Dual-Mode differential
Electrical	12V, 14Ah
Drive Train	Automatic torque-converter; forward, neutral, reverse
Suspension, front	Independent, MacPherson strut
Suspension, rear	Unit swing
Wheel travel, front	78mm
Wheel travel, rear	78.7mm
Steering	Rack & pinion
Tyre, front	22 x 9-10 (tubeless)
Tyre, rear	22 x 11-10 (tubeless)
Brakes, front	Dual hydraulic drums
Brakes, rear	Dual hydraulic drums
Turning radius	3,3m
Dimensions (L x W x H)	2,720 x 1,335 x 1,781mm
Cargo bed (L x W x H)	1,044 x 900 x 245mm
Wheelbase	1,779mm
Track width, front / rear	1,051/999mm
Ground Clearance	155mm
Vehicle Load Capacity	420kg
Cargo Bed Load Capacity	181kg
Curb Mass	429 kg
Towing Capacity	500kg
Fuel capacity	15,5 litres
Top speed	40km/h